



# 280C Dual Value Pack

**150 PSI / 2.96 CFM**

**Max. Amp Draw: 33 Amps**

**P/N 28002 - Black on Silver**

**NEW**

**COMING SOON**



280C Dual Performance Value Packs include two 280C compressors, two heavy duty 40-amp relays and a 110 PSI cut-on, 145 PSI cut-off pressure switch. Each Dual Performance Value Pack comes with remote mount filter assemblies and mounting hardware. Dual Performance Value Packs are rated to fill tank volumes up to 5 gallons.

**Note:** Use thread sealant for proper installation. Teflon tape is not recommended. Properly sealed, recommended torque is 12 to 15 ft. lbs.



List \$399.93 | Jobber \$279.95 | MAP \$279.95

## Features:

- (2) 280C Black on Silver Compressors
- (2) Air Filter Assemblies
- (2) Remote Mount Brackets
- (2) Sets of Remote Mount Fittings
- (2) Sets of Spare Air Filter Elements
- (2) Leader Hose Clips
- (6) Air Line Clips with Included Hardware
- (2) Heavy Duty 40-Amp Relays
- (1) One Heavy Duty Pressure Switch (110 PSI on, 145 PSI off)
- (2) Stainless Steel Braided Leader Hoses with Inline Check Valve
- Air Line (For Remote Mount Filter Installation)
- (8) Sets of Nuts, Bolts, Washers and Lock Washers

## Specifications:

- 12-Volt
- Permanent Magnetic Motor
- Duty Cycle: **30% @ 100 PSI**
- Max. Working Pressure: **150 PSI**
- Max. Air Tank: **5.0 Gallon**
- Min. Ambient Temp: **-40° F**
- Max. Ambient Temp: **158° F**
- Net Weight: 13.9 lbs.

## Dimensions:

(L) 198.12mm x (W) 100.33mm x (H) 161.29mm  
(L) 7.8" x (W) 3.95" x (H) 6.35"

## Performance Data

PSI	CFM	A	BAR	LPM	A
0	2.96	21	0	84.0	21
40	2.27	29	3	62.5	30
90	1.62	32	6	47.0	32
150	1.16	32	10	33.5	32

## Tank Fill Rates

2.0 Gallon Tank	Fill Rate
0 to 145 PSI	1 min. 34 sec. (± 10 sec.)
110 to 145 PSI	29 sec. (± 05 sec.)
2.5 Gallon Tank	Fill Rate
0 to 145 PSI	1 min. 57 sec. (± 10 sec.)
110 to 145 PSI	36 sec. (± 05 sec.)
5.0 Gallon Tank	Fill Rate
0 to 145 PSI	3 min. 54 sec. (± 15 sec.)
110 to 145 PSI	1 min. 11 sec. (± 10 sec.)

## Applications include:

